

 <p>SH9.5k-A1</p>	Product Description					Payment		30% IN ADVANCE BALANCE BEFORE SHIPMENT		DELIVERY TIME	
	Single Rated Line Pull 9500 lbs. (4310 kgs.)					e		CE			25
	Motor: 5.5hp/4.0kw, Series Wound DC 12V/24V					Pack Type	Case	Pack size	FOB		
	Control: Remote switch, 12feet(3.7m) lead					Carton	1/CTN	65*19*47	Ningbo		
	Gear Train: 3-Stage Planetary										
	Clutch: Sliding Ring Gear										
	Brake Action: Automatic in-the-drum										
	Drum Size Diameter(63.5mm),Length 8.8" (224mm.)										
	Cable: (28m of 8.3mm diameter)										
	Fairlead: 4-way roller fairlead										
Recommended Battery: 650 CCA minimum for winching											
Battery Leads: 2 gauge, 72" (1.83m)											
Weight: N.W.84lbs(38kg), G.W.86lbs(39kg)											
overall Dimensions (LxWxH)21.3"x 6.3" x 8.6"(552mmX160mmX218mm)											
Line pull LBS.<Kgs>	line speed FPM.<MPM>	Motor current Amps	Layer of cable	Rated line Pull Lbs<Kgs>	Total Rope on Drmt Ft<M>						
0<0>	8.2<2.5>	70	1	9500<4300>	16<5.0>						
2000<907>	6.9<2.1>	145	2	7700<3480>	42<12.0>						
4000<1814>	5.2<1.6>	210	3	6500<2940>	72<21.0>						
6000<2722>	3.9<1.2>	280	4	5700<2580>	94<28.0>						
8000<3629>	7.7<2.15>	350									
9500<4300>	7.0<1.95>	415									

